



INTÉRIOR FINISH

FURRING 1"X3" HOR. 16" c/c
GYPSUM 1/2" MIN.

HEADER JOIST 2" X 10" MIN.

JOIST HANGER

WOOD FLOOR SUPPORT

REINFORCING STEEL
HORIZONTAL AND VERTICAL
AS PER CODES
AND REGULATIONS
OR BY STRUCTURAL ENGINEER

INTÉRIOR FINISH
FURRING 1"X3" VER. 16" c/c
GYPSUM 1/2" MIN.

POLYCRETE BIG BLOCK 1600-6"
REGULAR 24" X 96"

4" (100mm) CONCRETE SLAB
WIREMESH OR
STRUCTURAL FIBER
2 1/2" (64) INSULATION PANEL

CONTINUOUS CONCRETE FOOTING
20 mPa - 14 mm AGGREGATES
REINFORCING STEEL:
3 CONTINUOUS 10M
15M TRANSVERSAL 16" C/C
DOWEL L 15M STAGGERED 16" C/C

EXTERIOR SIDING

FURRING 1" X 3" @ 16" C/C

POLYCRETE BIG BLOCK 1600-6"
REGULAR 24" X 96"

FLASHING

ACRYLIQUE PARGING
OR EQUIVALENT

BACKFILL SOIL
SLOPE OF 2% MIN.

WATERPROOF MEMBRANE
OR EQUIVALENT
*NOTE: Sheathing 7/16" (optional)
as a membrane protection*

GEOTEXTILE MEMBRANE

CRUSHED STONE 3/4"

PERFORATED DRAIN



TITLE:

Big Block 1600-6" regular 143 mm (5-5/8") of concrete, with wood floor on wood floor support (siding finish)

DRAWING NO:

BB-06-S2003-EN

DATE

2012-03-12

DISCLAIMER NOTICE

SPECIFIC INFORMATION REQUIRED FOR COMPLIANCE WITH LOCAL CODES IS THE RESPONSABILITY OF THE DESIGNER.

DRAWING BY:

AG

REV. NO:

REV. DATE: